



USK BEARING COMPANY



6313 6314 6315- O&Kai Z1V1 Z2V2 Z3V3 ISO
 Deep Groove Ball Bearing SKF NSK NTN NACHI
 Koyo OEM

Bearing No. 6313

6313 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 65x140x33 mm |
| Bore Diameter | 65 mm |
| Outer Diameter | 140 mm |
| Width | 33 mm |
| d | 65 mm |
| D | 140 mm |
| B | 33 mm |
| C | 33 mm |
| r min. | 2.1 mm |
| da min. | 77 mm |
| Da max. | 128 mm |
| ra max. | 2.0 mm |
| Weight | 2.08 Kg |
| Basic dynamic load rating (C) | 92,5 kN |
| Basic static load rating (C0) | 59,5 kN |
| (Grease) Lubrication Speed | 4700 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |



USK BEARING COMPANY

| | |
|---------------------------------|--|
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 65MM Bore; 140MM Outside Diameter; 33MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage |
| Other Features | Deep Groove |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nachiamerica.com |
| Weight / LBS | 4.885 |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outer Race Width | 1.299 Inch 33 Millimeter |
| Bore | 2.559 Inch 65 Millimeter |
| Outside Diameter | 5.512 Inch 140 Millimeter |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 65 mm |
| Width | 33 mm |
| Fillet Radius/Chamfer | 2.1 mm |
| | |



USK BEARING COMPANY

| | |
|-------------------------|-------------------|
| Dynamic Load Rating | 92,500 N |
| Static Load Rating | 59,500 N |
| Limiting Speed - Grease | 4,900 rpm |
| Limiting Speed - Oil | 6,000 rpm |
| Factor f_0 | 13.2 |
| Radial Clearance | 0.008 to 0.028 mm |
| d_a (min) | 77 mm |
| D_a (max) | 128 mm |
| r_a (max) | 2 mm |